

Webbing Pole Strap - Double Action Snap Hooks with Stainless Steel Adjuster

SPECIFICATION FOR 916241



Double Action Snap Hook: made of forged alloy steel, MBS 23kN. Gate opening 20mm, with golden yellow galvanised finish. ANSI Z359.12-2009 - 16kN gate










Abrasion Resistant Covering: prevents the webbing from being damaged by metallic contact of the connector.





Large Stainless Adjuster Set: made of 304 Stainless steel, MBS 15kN, with Nickel-chromed finish. Male and female buckle set with large webbing tab to allow for adjustment while working with gloves.



Security Stitch: Extra security stitch to ensure the snap hook can not roll back onto the webbing and open accidentally.

REF.	916241		
AS/NZS	AS 1891.5:2020		
 Number of users Max user weight	X 1		
	140 kg's		
LG	Adjustable Length 1 m - 2.5 m		
MAT.	 44 mm ± 1mm Polyester		
R (kN) / MFD	12 kN	/	≤ 600mm
	AUSTLIFT YSB024 / YSB025 - ANSI 		
	PN 145 - ANSI Z359.12-2009		PN 145 - ANSI Z359.12-2009
	1.3 KG		

		R (kN)	/	MFD
Rope / Webbing Adjuster	Harness connector	Static strength (Static load applied to pole strap)	/	Maximum Fall Distance (Maximum distance allowed to fall on pole strap as per AS/NZS 1891.4 guidelines)