

CROSS ARM ANCHOR STRAP

SPECIFICATION FOR 915720 AND 915721

The interlocking and reinforced webbing anchor strap is made of 44mm wide polyester webbing and stitched with 70mm webbing at the back for extra protection. Has a small d-ring on one end & a bigger d-ring on the other.







Small Flat D-ring: made of stamped alloy steel, MBS 23kN, with golden yellow galvanised finish and is proof load tested.

Anchor Strap Webbing: made of 44mm wide polyester webbing and stitched with 70mm webbing at the back for extra protection.

Large round D-ring: made of forged alloy steel, MBS 23kN, with golden yellow galvanised finish and is proof load tested.



REF.	915720	915721
AS/NZS	AS/NZS 5532:2013	
	X 1	
LG	1.5 m	0.7 m
MAT.	 45 mm PES	
R (kN) / MBS (kN)	15 kN / 26 kN	
	0.31 KG	0.25 KG
W.L.L	750 kg's	

W.L.L		R (kN) / MBS (kN)
Work Load Limit of Anchor Strap	Number of users	Static strength as per AS/NZS 5532 / Minimum Breaking Strength

NSW Head Office
 43 Frank Street
 Wetherill Park, NSW 2164
 02 9757 2277

WA Office
 42 Mulgool Road
 Malaga, WA 6090
 08 9248 6674

QLD Office
 7 Durbell Street
 Acacia Ridge, QLD 4110
 07 3272 0777

VIC Office
 47 Technology Drive
 Sunshine West, VIC 3020
 03 9314 5525