

FULL BODY HARNESS / HOT WORKS

SPECIFICATION FOR 9150016

1. Permanent Upright Dorsal D-ring: Stamped Stainless Steel with Splitted Polymer Sleeve which prevents the webbing from being damaged by the metallic contact of dorsal D-ring. MBS 23kN. Proof Load Tested.



2. Adjustable Buckle: provided with pull grip feature to enable easy pull down with thumb and easy to adjust straps for a good lift.



3. Retrieval attachment confine space shoulder loops


4. Combination Buckle: Stainless Steel, MBS 15kN



5. Product Label: with protection sleeve.

6. Fall arrest & Retrieval attachment loops: The loops at the ends are protected by an abrasion resistant covering. This prevents the webbing from being damaged by the metallic contact of the connector.

7. Aramid Webbing: Made with kevlar or equivalent core and aramid fibre outer covering. High heat aramid thread used to help keep welding and grinding sparks damage to a minimum.



REF.

9150016

SIZES

Standard = M-XL

KG

MAX. 140 KG

(Instruction Manual - HLPN-2021-V1.2)

AS/NZS

AS/NZS 1891.1:2020

Attachment

Dorsal D-Ring (A), Lower Sternal Webbing (A) - use both loops together




2 / 3

MAT. /

/

MAT. 45 mm

Aramid fibre heat resistant webbing



Not Fitted

Can be bought as an add on - 915075

kg

1.35 KG



YES

SIZES

KG

Number of adjustment buckles / automatic buckles



Confined Space Loops

MAT. /

Material of rings / buckles



Suspension Trauma Straps

Size Max. user weight

NSW Head Office

43 Frank Street
 Wetherill Park, NSW 2164
 02 9757 2277

WA Office

42 Mulgool Road
 Malaga, WA 6090
 08 9248 6674

QLD Office

7 Durbell Street
 Acacia Ridge, QLD 4110
 07 3272 0777

VIC Office

47 Technology Drive
 Sunshine West, VIC 3020
 03 9314 5525