

Sharp edge Inertia Reel / Retractable Block

SPECIFICATION FOR 915342 (2m)



Top Hook: Can be used as a Single & Forked Lanyard with Twin Connectors (915600).



Polymer Casing Casing is made of High Impact Strength Polymer to prevent breakage and is nearly indestructible.



Inbuilt Textile Energy Absorber with removable protective cover.



Retractable Webbing: 20mm Width.



Steel Quarter Turn-Locking Karabiner: made of forged alloy steel with golden yellow finish, Gate Opening: 10.5mm, MBS 25kN.

REF.	915342
LG. 	2 m
KG	MAX 140 KG / 100 KG (OVER A EDGE)
CE / AS/NZS	EN 360:2002 / AS/NZS 1891.3:2020
MAT. 	Polyamide 6 - 30% fiber glass
	STEEL Top Karabiner to be purchased separate / ANSI Triplock Karabiner
	X 1 / Yes with 915600 connector
R(kN)	15 kN
	YES - 100 KG
+	ATEX directive 2014/34/UE (II2 G Exh IIC T6 Gb).
	Less than 0.6kg without metal components 1.20 KG Total

LG. 		MAT. 		
Length Max. user weight	Number of swivels	Material of casing / webbing	Approved for work near sharp edges	Material of top connector / bottom connector
			Twin Use Approved	