43 Frank Street, Wetherill Park, NSW 2164 Tel: 02 9757 2277 Fax: 02 9757 2922



G70 SLIP HOOK

SPECIFICATION FOR 8MM TO 10MM





Clevis slip hooks combined with Grade 70 chain are an effective way to restraint heavy loads for transport operations with the benefit of a hook style fitting for all sorts of lashing applications

- Manufactured from forged steel, quenched, tempered and gold zinc plated.
- · Marked with chain size, lashing capacity, grade, batch numbered and branded Austlift for traceability.
- Batch test certificate available upon request.









Application

Use with Grade 70 Chain for restraining and lashing applications.


Specifications Material Grade 70 Material


Gold Zinc Plated **Finish**

Markings (as per AS 4344):

• B : Grade 70 Material | Batch Number

• C : Lashing Capacity • D : Austlift Logo





AS/NZS 4344	Size from (mm)	G70
----------------	----------------	------------

WARNING

G70 chain & fittings not to be used for lifting purposes.

SIZE (mm)	CODE	LC (T)	ТҮРЕ	Wt. (kg)	DIMENSIONS (mm)							
					Α	В	В1	С	D	Т	т	W
6	201306	2.3	Clevis	0.22	99.5	19	30	66	7.8	9	11.4	69
8	201308	3.8	Clevis	0.33	110	26	32	74	9.9	11	13.4	80
10	201310	6.0	Clevis	0.50	126.5	30	38	85	12	12	15.5	95
13	201313	9.0	Clevis	1.23	167.5	42.5	49	103	16	19	19.6	121
SIZE (mm)	CODE	LC (T)	TYPE	Wt. (kg)	DIMENSIONS (mm)							
					A	E	;	С	D	Ø	н	w
8	201408	3.8	Eye	0.37	110	20	5	74	10	16	25	80

NSW Head Office

- 43 Frank Street Wetherill Park, NSW 2164
- № 02 9757 2277

- **WA Office**
- ம் 42 Mulgal Road Malaga, WA 6090
- © 08 9248 6674

QLD Office

© 07 3272 0777

- ☆ 475 Dohertys Road Truganina, VIC 3029
- © 03 9314 5525