

Sharp Edge Lanyard Single - Triple Action hooks

SPECIFICATION FOR 916204



Triple Action Locking Snap Hook:

made of forged alloy steel, MBS 23kN.
 Gate opening 19.5mm, with golden yellow
 galvanised finish.
 ANSIZ359.12-2009 - 16kN gate









Abrasion Resistant Covering: prevents the
 webbing from being damaged by metallic
 contact of the connector.



Integral energy shock absorber:: made of
 44mm wide webbing and is shrink wrapped.
 it reduces the impact of a fall to less than 6kN.



Plastic Rope Thimble: prevents the
 rope from being damaged by metallic
 contact or abrasion from the webbing

REF.	916204		
AS/NZS	AS 1891.5:2020		
 Number of users Min user weight / Clearance Max user weight / Clearance	X 1		
	60 kg's	Minimum Fall Clearance	5.3 m
	140 kg's	Minimum Fall Clearance	6.3 m
LG	Length 2m		
MAT.	Edge Safe Kernmantle Rope - diameter 11mm		
R (kN) / TOF (kN) / PDF (kN)	12 kN / ≥ 2kN / ≤ 6kN		
	 44 mm ± 1mm Polyester		
	PN 152AT - ANSI Z359.12-2009	 STEEL	PN 152AT - ANSI Z359.12-2009
 Kg	1.1 KG		



Width and Material of the
 energy absorber



Harness connector / Anchor connector

R (kN)

Static strength

(Static load applied to fully
 deployed lanyard)

/

TOF (kN)

Tear out Force

(Force required to activate
 shock pack)

/

PDF

Peak deceleration Force

(Maximum force applied to user
 during shock pack functioning)

NSW Head Office

43 Frank Street
 Wetherill Park, NSW 2164
 02 9757 2277

WA Office

42 Mulgal Road
 Malaga, WA 6090
 08 9248 6674

QLD Office

7 Durbell Street
 Acacia Ridge, QLD 4110
 07 3272 0777

VIC Office

475 Dohertys Road
 Truganina, VIC 3029
 03 9314 5525