43 Frank Street, Wetherill Park, NSW 2164 Tel: 02 9757 2277 Fax: 02 9757 2922



Double Sharp Edge Lanyard -**Triple Action hooks**

SPECIFICATION FOR 916209





Triple Action Locking Snap Hook: made of forged alloy steel, MBS 23kN. Gate opening 19.5mm, with golden yellow galvanised finish.

ANSIZ359.12-2009 - 16kN gate



Abrasion Resistant Covering: prevents the webbing from being damaged by metallic contact of the connector.



Integral energy shock absorber:: made of 44mm wide webbing and is shrink wrapped. it reduces the impact of a fall to less than 6kN.



Parking D-Ring: made of forged alloy steel, MBS 23kN, with golden yellow galvanised finish. ANSI Z359.12-2009 Used to park unused lanyard legs



Plastic Rope Thimble: prevents the rope from being damaged by metallic contact or abrasion from the webbing

5.3 m

916209 REF.

AS/NZS AS 1891.5:2020



Number of users Min user weight / Clearance Max user weight / Clearance

X 1 60 kg's Minimum Fall Clearance 140 kg's | Minimum Fall Clearance

6.3 m

LG

Length 2m

MAT.

Edge Safe Kernmantle Rope - diameter 11mm

R (kN) / TOF (kN) / PDF (kN)

 $12 \text{ kN} / \ge 2 \text{kN} / \le 6 \text{kN}$



₩144 mm ± 1mm Polyester



2 x **PN 145- ANSI** Z359.12-2009



DR 008 - ANSI Z359.12-2009



1.4 KG



R (kN)

PN 145- ANSI

Z359.12-2009

TOF (kN)

PDF

Width and Material of the

Static strength

Tear out Force

Peak deceleration Force

energy absorber

(Static load applied to fully deployed lanyard)


(Force required to activate shock pack)

(Maximum force applied to user during shock pack functioning)









NSW Head Office

- 43 Frank Street Wetherill Park, NSW 2164
- 02 9757 2277

WA Office

- 42 Mulgal Road Malaga, WA 6090
- 08 9248 6674

OLD Office

- 7 Durbell Street Acacia Ridge, QLD 4110
- 07 3272 0777

VIC Office

- 475 Dohertys Road Truganina, VIC 3029
- 03 9314 5525