

EWP Heavy Duty Inertia Reel / Retractable Block

SPECIFICATION FOR 915343 (1.8m)



Top Hook: Can be used as a Single & Forked Lanyard with Twin Connectors (915600).



Polymer Casing Casing is made of High Impact Strength Polymer to prevent breakage and is nearly indestructible.



Inbuilt Textile Energy Absorber with removable protective cover.



Retractable Webbing: 20mm Width.



Steel Quarter Turn-Locking Karabiner: made of forged alloy steel with golden yellow finish, Gate Opening: 10.5mm, MBS 25kN.

REF.	915343
LG. 	1.8 m
CE / AS/NZS	EN 360:2002 / AS 1891.3:2020 Amd 1:2021 (BMP No. 739186)
MAT. 	Polyamide 6 - 30% fiber glass
	STEEL Top Karabiner to be purchased separate / ANSI Triplock Karabiner
360°	X 1 / Yes with 915600 connector
R(kN)	15 kN
	YES - 100 KG
+	ATEX directive 2014/34/UE (II2 G Exh IIC T6 Gb).
	Less than 0.6kg without metal components 1.20 KG Total

LG. 	360° Number of swivels	MAT. 	Approved for work near sharp edges	Material of top connector / bottom connector
Length Max. user weight		Material of casing / webbing	Twin Use Approved	